TECHNICAL DATA SHEET (TDS)



USTAFIX WALLPAPER ADHESIVE

1 - DESCRIPTION

Ustafix Wallpaper Adhesive is a cellulosic polymer based, water soluble powder used in sticking of cellulose based paper materials.

2 - PROPERTIES

- Easy to apply.
- Allows time for positioning.
- Makes future removal quick and easy.
- Dissolves in water with ease.
- Can be cleaned with a sponge and water

3 - APPLICATIONS

Sticking wallpapers, pre-pasted borders, posters, placards etc.

4 - INSTRUCTIONS

Add the adhesive slowly, in preferably warm, water in accordance with the figures shown below. Stir the mixture and allow the adhesive dissolve in the water. Make sure that substrates are clean, dry and smooth. Roll the mixture to the back of wallpapers.

5- PACKAGING

Product	Weight	Package
Wallpaper Adhesive	500 gr.	24
Wallpaper Adhesive	1000 gr.	12

6- STORAGE AND SHELF LIFE

24 months in unopened cartridge if stored under dry and cool conditions

7- SAFETY

- Must be used in well ventilated areas.
- Must be kept away from children.

TECHNICAL DATA SHEET (TDS)



8- TECHNICAL PROPERTIES

Basis	: Carboxymethyl cellulose	
Appearance	: Powder	
Colour	: White to creamy	
Viscosity	: 200 - 250 cP	cps at 25°C (Spindle No 2, 60 rpm)
Moisture (105 °C)	: Max %12	
Active Matter	: %60 ± 2	
Degree of Substitution	: 0.7 – 0.9	
Total Salts	: %40 ± 2	
pH (%1)	: 8 - 10	

Application Ratios

For 200g s of adhesive

Paper Type	Amount of water	Roll	Surface
Light paper	6,5 liter	4-5	20-25 m ²
Normal paper	5,0 liter	3-4	15-20 m ²
Heavy paper	3,6 liter	2-3	13-18 m ²